

EAGLE INDUSTRIES

www.eagleind.com 800.266.8246

BLAST PAK AIR DRYER

PORTABLE COMPRESSED AIR SYSTEM

SPECIFICATIONS

Air Drying Process



- * FREE INITAL DESICCANT FILL
- * 10 YEAR VESSEL WARRANTY



250 CFM 400 CFM 800 CFM 1200 CFM 1600 CFM (Custom Systems Available)

- Operates with compressed air temperatures up to 250°F
- Steel skid forklift channels and lifting lugs for portability
- Air motor includes filter, regulator, lubricator and muffler
- Epoxy internal dryer coating for long vessel life
- Optional pneumatic demand drain prevents air loss
- · Downstream particular filter with permanent stainless stell mesh
- Two dryer sight windows for desiccant level viewing

To the best of our knowledge, these are typical property values & are intended as guides only, not as specification limits. Eagle Industries of Louisiana, Inc. makes no warranties as to the fitness for a specific use or merchantability of products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations, & disclaims all liability for resulting loss or damage.


EAGLE INDUSTRIES


www.eagleind.com 800.266.8246

BLAST PAK AIR DRYER

PORTABLE COMPRESSED AIR SYSTEM

SPECIFICATIONS





DIMENSIONS	FD-250	FD-400	FD-800	FD-1200	FD-1600
PART NUMBER	80-1456	80-1430	80-1431	80-1416	80-1347
HEIGHT	77"	77"	83 - 3/4"	88"	94 - 1/2"
INLET HEIGHT	71 - 9/16"	72 - 1/8"	78 - 3/8"	82 - 5/8"	89 - 3/8"
DEPTH	27"	26"	32 - 7/8"	32 - 7/8"	43"
OUTLET HEIGHT	58 - 1/2"	58 - 9/16"	59 - 1/2"	60"	59 - 1/8"
WIDTH	48"	49"	54"	60"	71 - 1/2"
INLET SIZE	1-1/2" NPT(F)	2" NPT(F)	2-1/2" NPT(F)	2-1/2" NPT(F)	3" NPT(F)
OUTLET SIZE	1-1/2" NPT(F)	2" NPT(F)	2-1/2" NPT(F)	3" NPT(F)	3" NPT(F)
WEIGHT	660 lbs	760 lbs	1155 lbs	1525 lbs	1875 lbs
AIR MOTOR SCFM	17	25	70	70	150

To the best of our knowledge, these are typical property values & are intended as guides only, not as specification limits. Eagle Industries of Louisiana, Inc. makes no warranties as to the fitness for a specific use or merchantability of products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations, & disclaims all liability for resulting loss or damage.